

# tasker®

Shielded twisted pair cables sect. 0,22 mm<sup>2</sup>

RoHS  
Conformity

**Applications:**

Braided shielded twisted pair cables for data transmission and electronics.

**Characteristics:**

Conductors: stranded in O.F.C.  
tinned copper  
Cond. insulation: PVC  
Twisted pair: 30 Twist/mt  
Pair colours: White/grey, White/yellow,  
White/red, White/green,  
White/blue, White/brown,  
White/black, Yellow/grey,  
Yellow/red, Yellow/green,  
Yellow/blue, Yellow/brown,  
Yellow/black

Total Shield: Braided covering 85%  
O.F.C. tinned copper

External Sheath: PVC  
Sheath colour: Grey

Max rated Voltage AC: 49 V.  
Operative Temperature °C.: -15° / +70°



tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C184	2x2	2 x 2 x 0,22 (24 AWG)	7x0,20	1,2		5,8	100	B	5,0
C194	3x2	3 x 2 x 0,22 (24 AWG)	7x0,20	1,2		6,6	100	B	6,0
C185	4x2	4 x 2 x 0,22 (24 AWG)	7x0,20	1,2		6,8	100	B	7,0
C186	6x2	6 x 2 x 0,22 (24 AWG)	7x0,20	1,2		8,5	100	B	10,0
C187	8x2	8 x 2 x 0,22 (24 AWG)	7x0,20	1,2		9,0	100	B	11,0
C188	10x2	10 x 2 x 0,22 (24 AWG)	7x0,20	1,2		9,8	100	B	12,0
C189	12x2	12 x 2 x 0,22 (24 AWG)	7x0,20	1,2		10,5	100	B	15,0
C190	13x2	13 x 2 x 0,22 (24 AWG)	7x0,20	1,2		11,0	100	B	15,5

Notes:

Conductor Resistance	Capacity Core/core	Capacity Core/shield
Ω/Km ± 5%	pF/mt	pF/mt
90	120	180
90	110	170
90	110	160
90	100	150
90	100	150
90	90	150
90	90	140
90	90	140